(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 28 July 2005 (28.07.2005)

PCT

(10) International Publication Number WO 2005/069366 A1

(51) International Patent Classification7: G02F 1/1333

H01L 21/68,

(21) International Application Number:

PCT/JP2005/000712

(22) International Filing Date: 13 January 2005 (13.01.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2004-009021

16 January 2004 (16.01.2004)

(71) Applicant (for all designated States except US): SHARP KABUSHIKI KAISHA [JP/JP]; 22-22, Nagaike-cho, Abeno-ku, Osaka-shi, Osaka, 5458522 (JP).

(75) Inventor/Applicant (for US only): MIYAKE, Hidetomo [JP/JP]; 719-1, Maenoheta-cho, Matsusaka-shi, Mie, 5150045 (ЛР).

(74) Agents: MAEDA, Hiroshi et al.; Osaka-Marubeni Bldg., 5-7, Hommachi 2-chome, Chuo-ku, Osaka-shi, Osaka 5410053 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SUBSTRATE ADSORPTION DEVICE AND SUBSTRATE BONDING DEVICE



(57) Abstract: A substrate adsorption device 1 includes: a stage 11 having an adsorption face 12 for holding a substrate 20; a plurality of adsorption ports 13 formed in a region of the adsorption face 12 of the stage 11; and a vacuum pump 14 connected to each adsorption port through an air discharge path 17. A pressure sensor 18 for detecting the pressure in the air discharge path 17 is provided, and a plurality of leak trenches 30 open to both the adsorption face 12 of the stage 11 and a side face of the stage 11 are formed in a region of the stage 11 except the region where the adsorption ports 13 are formed. With such a low-cost and simple structure; a foreign matter 15, which is a factor of inviting damage to the substrate 20, is detected, to prevent damage to the substrate 20.